according to Regulation (EC) No. 1907/2006 (REACH)

Trade name: VEG001

Revision date: 04.07.2025 **Version (Revision):** 3.0.0 (2.0.0)

Print date: 04.07.2025

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

VEG001

Unique Formula Identifier: SC00-60J5-P007-GD93

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Metal working fluids

Lubrication at high energy conditions in metal working operations

Uses advised against

No information available.

1.3 Details of the supplier of the safety data sheet

Supplier (manufacturer/importer/downstream user/distributor)

CNCmarket.de (E4B2B GmbH)

Street: Heisenbergstraße 5

Postal code/City: 10587 Berlin

Telephone: +49 15888 725497

E-mail address: kontakt@cncmarket.de

1.4 Emergency telephone number

+49 55119240 (GIZ-Nord Poisons Center: 24h/7d)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Eye Irrit. 2 ; H319 - Serious eye damage/eye irritation : Category 2 ; Causes serious eye irritation.

Skin Sens. 1; H317 - Skin sensitisation: Category 1; May cause an allergic skin reaction.

Aquatic Chronic 3; H412 - Hazardous to the aquatic environment: Chronic 3; Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



Exclamation mark (GHS07)

Signal word

Warning

Hazard components for labelling

1,2-BENZISOTHIAZOL-3(2H)-ONE; CAS No.: 2634-33-5 2-n-butyl-benzo[d]isothiazol-3-one; CAS No.: 4299-07-4

Hazard statements

H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

Page: 1 / 12

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name: VEG001

Revision date: 04.07.2025 **Version (Revision):** 3.0.0 (2.0.0)

Print date : 04.07.2025

P264 Wash hands thoroughly after handling.

P272 Contaminated work clothing should not be allowed out of the workplace.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.

2.3 Other hazards

Adverse environmental effects

Contains no substance(s) known to have endocrine disrupting properties.

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description

Mixture of substances listed below with nonhazardous additions.

Hazardous ingredients

2,2'-(METHYLIMINO)DIETHANOL; REACH No.: 01-2119488970-24-XXXX; EC No.: 203-312-7; CAS No.: 105-59-9

Weight fraction : \geq 5 - < 10 % Classification 1272/2008 [CLP] : Eye Irrit. 2 ; H319

2-PHENOXYETHANOL; REACH No.: 01-2119488943-21-0000; EC No.: 204-589-7; CAS No.: 122-99-6

Weight fraction : $\geq 1 - < 3 \%$

Classification 1272/2008 [CLP] : Eye Dam. 1 ; H318 Acute Tox. 4 ; H302 STOT SE 3 ; H335

Specific Conc. Limits: (ATE - oral: 1394 mg/kg)

Alcohols, C16-18 and C18-unsatd., ethoxylated; REACH No.: 01-2119489407-26; EC No.: 500-236-9; CAS No.: 68920-66-1

Weight fraction : $\geq 1 - < 2.5 \%$

Classification 1272/2008 [CLP]: Skin Irrit. 2; H315 Aquatic Chronic 2; H411

1H-BENZOTRIAZOLE (1,2,3); REACH No.: 01-2119979079-20-XXXX; EC No.: 202-394-1; CAS No.: 95-14-7

Weight fraction : \geq 1 - < 2,5 %

Classification 1272/2008 [CLP] : Acute Tox. 4 ; H302 Eye Irrit. 2 ; H319 Aquatic Chronic 2 ; H411

1,2-BENZISOTHIAZOL-3(2H)-ONE; REACH No.: 01-2120761540-60-XXXX; EC No.: 220-120-9; CAS No.: 2634-33-5

Weight fraction : $\geq 0.25 - < 0.5 \%$

Classification 1272/2008 [CLP]: Eye Dam. 1; H318 Acute Tox. 4; H302 Skin Irrit. 2; H315 Skin Sens. 1;

H317 Aquatic Acute 1; H400 Skin Sens. 1; H317: C ≥ 0,05 %

 $\hbox{2-n-butyl-benzo[d]} is othiazol-\hbox{3-one} \; ; \; \hbox{EC No.} \; : \; 420-590-7; \; \hbox{CAS No.} \; : \; 4299-07-4$

Weight fraction : \geq 0,1 - < 0,25 %

Classification 1272/2008 [CLP]: Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Acute 1;

H400 Aquatic Chronic 1; H410

Specific Conc. Limits : (M Chronic=1) • (M Acute=10)

Additional information

Specific Conc. Limits:

For full text of Hazard- and EU Hazard-statements: see SECTION 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

Remove victim out of the danger area. When in doubt or if symptoms are observed, get medical advice.

Following inhalation

Remove casualty to fresh air and keep warm and at rest.

In case of skin contact

Change contaminated, saturated clothing. After contact with skin, wash with plenty of water and soap. In case of skin irritation, consult a physician.

Page: 2 / 12

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name: VEG001

Revision date: 04.07.2025 **Version (Revision):** 3.0.0 (2.0.0)

Print date : 04.07.2025

After eye contact

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Following ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention.

4.2 Most important symptoms and effects, both acute and delayed

No information available.

4.3 Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Foam, Extinguishing powder, Carbon dioxide (CO2), Water spray jet, Water mist, Sand,

Unsuitable extinguishing media

Strong water jet

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

In case of fire may be liberated: Carbon dioxide (CO2), Carbon monoxide, Nitrogen oxides (NOx), Smoke and other incomplete combustion products.

5.3 Advice for firefighters

Special protective equipment for firefighters

Wear self-contained breathing apparatus.

5.4 Additional information

Do not inhale explosion and combustion gases.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Use personal protection equipment. Avoid contact with skin, eyes and clothes. Wear breathing apparatus if exposed to vapours/dusts/aerosols. Ventilate affected area.

6.2 Environmental precautions

Cover drains. Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Make sure spills can be contained, e.g. in sump pallets or kerbed areas.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3 Methods and material for containment and cleaning up

For containment

Cover drains. Stop and contain spill/release if it can be done safely. If this cannot be done, allow fire to burn under control. Prevent spread over a wide area (e.g. by containment or oil barriers).

For cleaning up

Wipe up with absorbent material (eg. cloth, fleece). Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Take up mechanically, placing in appropriate containers for disposal. Clean contaminated articles and floor according to the environmental legislation.

6.4 Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

Page: 3 / 12

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name: VEG001

Revision date: 04.07.2025 **Version (Revision):** 3.0.0 (2.0.0)

Print date: 04.07.2025

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Wear personal protection equipment (refer to section 8). Use only in well-ventilated areas. Handle and open container with care. Avoid contact with skin, eyes and clothes. Do not breathe gas/fumes/vapour/spray.

Protective measures

Measures to prevent fire

Usual measures for fire prevention.

Environmental precautions

Do not allow to enter into surface water or drains.

Advices on general occupational hygiene

When using do not eat, drink, smoke, sniff. Wash hands before breaks and after work. Do not put any productimpregnated cleaning rags into your trouser pockets.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place. Only use containers specifically approved for the substance/product. Protect containers against damage.

Hints on joint storage

Keep away from: Oxidizing agent

Storage class: 10

Storage class (TRGS 510): 10 **Do not store together with** Food and feedingstuffs

Further information on storage conditions

Recommended storage temperature: 5 - 40°C / 40 - 105°F.

Protect against: Frost Heat. UV-radiation/sunlight

Storage stability: Product may be stored for up to 12 months under described conditions.

7.3 Specific end use(s)

None

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

2,2`,2``-NITRILOTRIETHANOL; CAS No.: 102-71-6
Limit value type (country of origin): AGW (D)
Limit value: 5 mg/m³

Version:

Limit value type (country of origin): TRGS 900 (D)

Parameter: E: inhalable fraction

Limit value: 1 mg/m³
Peak limitation: 1(I)
Remark: Y
Version: 12.06.2023
2-PHENOXYETHANOL; CAS No.: 122-99-6

Limit value type (country of origin) : TRGS 900 (D) Limit value : 1 ppm / 5,7 mg/m³

Peak limitation : 1(I) Remark : Y

Version: 12.06.2023

DNEL-/PNEC-values

Page: 4 / 12

(EN/D)

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : VEG001

Revision date: 04.07.2025 **Version (Revision):** 3.0.0 (2.0.0)

Print date : 04.07.2025

DNEL/DMEL

2,2´-(METHYLIMINO)DIETHANOL; CAS No.: 105-59-9
Limit value type: DNEL worker (systemic)

Exposure route: Dermal
Exposure frequency: Long-term
Limit value: 19 mg/kg bw/d
Limit value type: DNEL worker (systemic)

 $\begin{tabular}{lll} Exposure route: & Inhalation \\ Exposure frequency: & Long-term \\ Limit value: & 26 mg/m^3 \\ 2,2`,2``-NITRILOTRIETHANOL; CAS No.: 102-71-6 \\ \end{tabular}$

Limit value type: DNEL worker (systemic)
Exposure route: Dermal
Exposure frequency: Long-term
Limit value: 6,3 mg/kg bw/d

Limit value type : DNEL worker (systemic)

Exposure route: Inhalation
Exposure frequency: Long-term
Limit value: 5 mg/m³
2-PHENOXYETHANOL; CAS No.: 122-99-6

Limit value type : DNEL worker (systemic)

Exposure route : Dermal
Exposure frequency : Long-term
Limit value : 34,72 mg/kg

Limit value type : DNEL worker (systemic)

Exposure route: Inhalation
Exposure frequency: Long-term
Limit value: 8,07 mg/m³
1H-BENZOTRIAZOLE (1,2,3); CAS No.: 95-14-7

Limit value type : DNEL worker (systemic)

Exposure route : Dermal

Exposure frequency : Long-term

Limit value : 1,08 mg/kg bw/d

Limit value type : DNEL worker (systemic)

Exposure route : Inhalation
Exposure frequency : Long-term
Limit value : 10 mg/m³

Remark

The DNEL may differ from an Occupational Exposure Limit (OEL) for the same chemical. OELs are considered to be safe exposure levels for a typical worker in an occupational setting for an 8-hour work shift, 40 hour work week, as a time weighted average (TWA) or a 15 minute short-term exposure limit (STEL). The Derived No Effect Level (DNEL) is an estimated safe level of exposure that is derived from toxicity data in accord with specific guidance within the European REACH regulation.

PNEC

2,2'-(METHYLIMINO)DIETHANOL; CAS No.: 105-59-9

Limit value type : PNEC (Aquatic, freshwater)

Limit value : 0,1 mg/l

Limit value type : PNEC (Aquatic, marine water)

Limit value : 0,0045 mg/l

Limit value type : PNEC (Sediment, freshwater)

Limit value : 0,78 mg/kg
Limit value type : PNEC Soil, Freshwater

Limit value : PNEC 3011, Preshwater 0,097 mg/kg

Limit value type : PNEC (Sewage treatment plant)

Limit value: 10 mg/l 2,2`,2``-NITRILOTRIETHANOL; CAS No.: 102-71-6

Page: 5 / 12

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : VEG001

Revision date : 04.07.2025 **Version (Revision) :** 3.0.0 (2.0.0)

Print date : 04.07.2025

Limit value type : PNEC (Aquatic, freshwater)

Limit value: 0,32 mg/l

Limit value type : PNEC (Aquatic, marine water)

Limit value : 0,032 mg/l

Limit value type : PNEC (Sediment, freshwater)

Limit value : 1,7 mg/kg

Limit value type : PNEC (Sediment, marine water)

Limit value : 0,17 mg/kg
Limit value type : PNEC (Soil)
Limit value : 0,151 mg/kg
2-PHENOXYETHANOL ; CAS No. : 122-99-6

Limit value type : PNEC (Aquatic, freshwater)

Limit value : 0,943 mg/l

Limit value type : PNEC (Aquatic, marine water)

Limit value: 0,0943 mg/l

Limit value type : PNEC (Sediment, freshwater)

Limit value : 7,2366 mg/kg

Limit value type : PNEC (Sewage treatment plant)

Limit value : 24,8 mg/l 1H-BENZOTRIAZOLE (1,2,3) ; CAS No. : 95-14-7

Limit value type : PNEC (Aquatic, freshwater)

Limit value : 0,0194 mg/l

Limit value type : PNEC (Aquatic, marine water)

Limit value: 0,0194 mg/l

Limit value type : PNEC (Sediment, freshwater)

Limit value : 0,00375 mg/kg dw
Limit value type : PNEC (Soil)
Limit value : 0,003 mg/kg dw

Limit value type : PNEC (Sewage treatment plant)

Limit value: 39,4 mg/l

8.2 Exposure controls

Appropriate engineering controls

If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means. Technical measures and the application of suitable work processes have priority over personal protection equipment.

Personal protection equipment

Personal protective equipment selections vary based on potential exposure conditions such as applications, handling practices, concentration and ventilation. Information on the selection of protective equipment for use with this material, as provided below, is based upon intended, normal usage.

Eye/face protection

Eye glasses with side protection EN 166

Skin protection

Hand protection

Tested protective gloves must be worn: DIN EN 374

The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. Do not wear gloves near rotary machines and tools.

Suitable material:

Wearing time with permanent contact:

Material: NBR (Nitrile rubber), CR (polychloroprene, chloroprene rubber),

Thickness of the glove material: 0,70 mm

Breakthrough time (maximum wearing time): > 480 min

Wearing time with occasional contact (splashes):

NBR (Nitrile rubber), CR (polychloroprene, chloroprene rubber),

Thickness of the glove material: 0,40 mm

Breakthrough time (maximum wearing time): > 30 min

Page: 6 / 12

according to Regulation (EC) No. 1907/2006 (REACH)

VEG001

Revision date: 04.07.2025 Version (Revision): 3.0.0 (2.0.0)

Print date : 04.07.2025

Unsuitable material: PVA (Polyvinyl alcohol),

Breakthrough time (maximum wearing time): : For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Body protection: not required. If prolonged or repeated contact is likely, chemical, and oil resistant clothing is recommended.

Respiratory protection

Usually no personal respirative protection necessary. If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Respiratory protection necessary at: exceeding exposure limit values, insufficient ventilation, aerosol or mist formation.

Suitable respiratory protection apparatus

Combination filtering device

General information

When using do not eat, drink, smoke, sniff. Wash hands before breaks and after work. Wash contaminated clothing prior to re-use. Apply skin care products after work.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance: Liquid Colour: brown Odour: characteristic Safety characteristics

Melting point/freezing point: No data available Initial boiling point and boiling (1013 hPa) 100 °C range: Flammability: flammable Lower explosion limit: No data available Upper explosion limit: No data available

Flash point: 100 DIN EN ISO 2592

Auto-ignition temperature : No data available

Decomposition temperature: not determined

(20 °C / 5 Weight-% DIN 51369 9,3 Kinematic viscosity: (20°C) 177 DIN EN ISO 3104

Water solubility: (20°C) miscible log P O/W: not applicable (20°C) No data available Vapour pressure:

1,015 **DIN FN ISO 12185** Density: (15°C) g/cm³

mm²/s

Relative vapour density: (20°C) No data available

Maximum VOC content 0 Weight-% (Switzerland):

9.2 Other information

None

SECTION 10: Stability and reactivity

10.1 Reactivity

No information available.

10.2 Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3 Possibility of hazardous reactions

Page: 7 / 12

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : VEG001

Revision date: 04.07.2025 **Version (Revision):** 3.0.0 (2.0.0)

Print date : 04.07.2025

No hazardous reaction when handled and stored according to provisions.

10.4 Conditions to avoid

No information available.

10.5 Incompatible materials

Oxidising agent, strong.

10.6 Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicological data are not available. The statement is derived from the properties of the single components.

Acute toxicity

Based on available data, the classification criteria are not met.

Acute oral toxicity

Parameter: LD50 (2,2 '-(METHYLIMINO)DIETHANOL; CAS No.: 105-59-9)

Exposure route: Oral
Species: Rat
Effective dose: 4680 mg/kg

Parameter: LD50 (2-PHENOXYETHANOL ; CAS No. : 122-99-6)

Exposure route: Oral
Species: Rat
Effective dose: 1850 mg/kg

Parameter: LD50 (Alcohols, C16-18 and C18-unsatd., ethoxylated ; CAS No.: 68920-66-1)

Exposure route : Oral Species : Rat

Effective dose: > 2000 mg/kg

Acute dermal toxicity

Parameter: LD50 (2,2'-(METHYLIMINO)DIETHANOL ; CAS No. : 105-59-9)

Exposure route : Dermal
Species : Rabbit
Effective dose : > 2000 mg/kg

Parameter: LD50 (2-PHENOXYETHANOL ; CAS No. : 122-99-6)

Exposure route : Dermal
Species : Rabbit
Effective dose : > 2000 mg/kg

Corrosion

Skin corrosion/irritation

Parameter: Skin corrosion/irritation (Alcohols, C16-18 and C18-unsatd., ethoxylated ; CAS No. :

68920-66-1)

Species: Rabbit
Result: irritating
Method: OECD 404

Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation

Parameter: Serious eye damage/eye irritation (2-PHENOXYETHANOL; CAS No.: 122-99-6)

Species: Rabbit
Result: Strongly irritant
Method: OECD 405

Parameter: Serious eye damage/eye irritation (Alcohols, C16-18 and C18-unsatd., ethoxylated;

CAS No.: 68920-66-1)

Species: Rabbit

Result: Mild effects but not relevant for classification.

Page: 8 / 12

(EN/D)

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name: VEG001

Revision date: 04.07.2025 **Version (Revision):** 3.0.0 (2.0.0)

Print date : 04.07.2025

Method: OECD 405

Irritating to eyes.

Respiratory or skin sensitisation

May cause sensitization by skin contact.

Skin sensitisation

Parameter: Skin sensitisation (2-PHENOXYETHANOL; CAS No.: 122-99-6)

Species: Guinea pig
Result: not sensitizing
Method: OECD 406

Parameter: Skin sensitisation (Alcohols, C16-18 and C18-unsatd., ethoxylated; CAS No.: 68920-

66-1)

Species: Guinea pig
Result: not sensitizing
Method: OECD 406

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Carcinogenicity

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

STOT SE 1 and 2

Based on available data, the classification criteria are not met.

STOT-repeated exposure

STOT RE 1 and 2

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met. For viscosity data, see section 9.

11.2 Information on other hazards

No information available.

SECTION 12: Ecological information

12.1 Toxicity

For the product ecotoxicological data are not available. The ecotoxicological properties of this mixture are determined by the ecotoxicological properties of the single components (see section 3).

Aquatic toxicity

Harmful to aquatic life.

Acute (short-term) fish toxicity

Parameter: LC50 (2,2'-(METHYLIMINO)DIETHANOL; CAS No.: 105-59-9)

Effective dose : 1466 mg/l Exposure time : 96 h

Parameter: LC50 (2-PHENOXYETHANOL ; CAS No. : 122-99-6)

Species: Pimephales promelas (fathead minnow)

Effective dose : 344 mg/l Exposure time : 96 h

Parameter: LC50 (Alcohols, C16-18 and C18-unsatd., ethoxylated; CAS No.: 68920-66-1)

Species: Danio rerio (zebrafish)

Effective dose: 10 - 100 mg/l

Exposure time: 96 h

Method: OECD 203

Page: 9 / 12

(EN/D)

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : VEG001

Revision date : 04.07.2025 **Version (Revision) :** 3.0.0 (2.0.0)

Print date : 04.07.2025

Acute (short-term) toxicity to crustacea

Parameter: EC50 (2,2'-(METHYLIMINO)DIETHANOL; CAS No.: 105-59-9)

Effective dose : 233 mg/l Exposure time : 48 h

Parameter: EC50 (2-PHENOXYETHANOL ; CAS No. : 122-99-6)

Species: Daphnia magna (Big water flea)

Effective dose : > 500 mg/l Exposure time : 48 h

Parameter: EC50 (Alcohols, C16-18 and C18-unsatd., ethoxylated; CAS No.: 68920-66-1)

Species: Daphnia magna (Big water flea)

Effective dose: 51 mg/l
Exposure time: 48 h
Method: OECD 202

Acute (short-term) toxicity to algae and cyanobacteria

Parameter: EC50 (2,2'-(METHYLIMINO)DIETHANOL; CAS No.: 105-59-9)

Effective dose : > 100 mg/l Exposure time : 72 h

Parameter: EC50 (2-PHENOXYETHANOL ; CAS No. : 122-99-6)

Species: Desmodesmus subspicatus

Effective dose: > 500 mg/l Exposure time: 72 h

Parameter: EC50 (Alcohols, C16-18 and C18-unsatd., ethoxylated; CAS No.: 68920-66-1)

Species : Scenedesmus subspicatus

Effective dose : > 100 mg/lExposure time : 72 h

12.2 Persistence and degradability

Part of the components is biodegradable.

12.3 Bioaccumulative potential

No indication of bioaccumulation potential.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6 Endocrine disrupting properties

No information available.

12.7 Other adverse effects

No information available.

12.8 Additional ecotoxicological information

Do not allow uncontrolled discharge of product into the environment.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Directive 2008/98/EC (Waste Framework Directive)

After intended use

Consult the appropriate local waste disposal expert about waste disposal. Dispose of waste according to applicable legislation.

Waste codes/waste designations according to EWC/AVV

12 01 10* synthetic machining oils

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

Additional information

Page: 10 / 12

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name: VEG001

Revision date: 04.07.2025 **Version (Revision):** 3.0.0 (2.0.0)

Print date : 04.07.2025

Non-contaminated packages may be recycled. Packing which cannot be properly cleaned must be disposed of. Dispose of waste according to applicable legislation.

SECTION 14: Transport information

14.1 UN number or ID number

No dangerous good in sense of these transport regulations.

14.2 UN proper shipping name

No dangerous good in sense of these transport regulations.

14.3 Transport hazard class(es)

No dangerous good in sense of these transport regulations.

14.4 Packing group

No dangerous good in sense of these transport regulations.

14.5 Environmental hazards

No dangerous good in sense of these transport regulations.

14.6 Special precautions for user

None

SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture $^{15.1}$

EU legislation

Authorisations and/or restrictions on use

Restrictions on use

Regulation (EC) No. 1907/2006 (REACH), Annex XVII (restrictions)

Use restriction according to REACH annex XVII, no.: 3

National regulations

Störfallverordnung (12. BImschV)

Not subject to StörfallVO.

Water hazard class

Classification according to AwSV - Class : 1 (Slightly hazardous to water)

Additional information

Berufsgenossenschaftliche Regeln (DGUV-Regeln)

The product corresponds with TRGS 611.

15.2 Chemical Safety Assessment

No information available.

SECTION 16: Other information

16.1 Indication of changes

None

16.2 Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)

Page: 11 / 12

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name: VEG001

Revision date: 04.07.2025 **Version (Revision):** 3.0.0 (2.0.0)

Print date: 04.07.2025

CAS: Chemical Abstracts Service (division of the American Chemical Society)

GHS: Globally Harmonized System on the Classification and Labelling of Chemicals

CLP: Regulation on Classification, Labelling and Packaging of Substances and Mixtures,

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

EC50: Effective concentration, 50 percent

DNEL: Derived No Effect Level

PNEC: Predicted No Effect Concentration PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

16.3 Key literature references and sources for data

Sources of information used in preparing this SDS included one or more of the following: Product Dossiers and SDS from suppliers, complemented by public sources, as appropriate (GESTIS, the EU IUCLID Data Base, U.S. NTP publications, e.g.).

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

No information available.

16.5 Relevant H- and EUH-phrases (Number and full text)

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.H411 Toxic to aquatic life with long lasting effects.

16.6 Training advice

Provide adequate information, instruction and training for operators.

16.7 Additional information

None

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

Page: 12 / 12