

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : BVR301
Revision date : 12.01.2024
Print date : 03.12.2025

Version (Revision) : 6.0.1 (5.0.1)

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

BVR301
Unique Formula Identifier : 5S00-R005-600Q-S36E

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Metal working fluids
Lubrication at high energy conditions in metal working operations

Uses advised against

No information available.

1.3 Details of the supplier of the safety data sheet

Supplier (manufacturer/importer/downstream user/distributor)

CNCmarket.de (E4B2B GmbH)

Street : Heisenbergstraße 5

Postal code/City : 10587 Berlin

Telephone : +49 15888 725497

E-mail address : kontakt@cncmarket.de

1.4 Emergency telephone number

+49 55119240 (GIZ-Nord Poisons Center: 24h/7d)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Skin Irrit. 2 ; H315 - Skin corrosion/irritation : Category 2 ; Causes skin irritation.
Eye Irrit. 2 ; H319 - Serious eye damage/eye irritation : Category 2 ; Causes serious eye irritation.
Skin Sens. 1 ; H317 - Skin sensitisation : Category 1 ; May cause an allergic skin reaction.

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



Exclamation mark (GHS07)

Signal word

Warning

Hazard components for labelling

1,2-BENZISOTHIAZOL-3(2H)-ONE ; CAS No. : 2634-33-5

Hazard statements

H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.

Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : BVR301
Revision date : 12.01.2024
Print date : 03.12.2025

Version (Revision) : 6.0.1 (5.0.1)

P264 Wash hands thoroughly after handling.
P272 Contaminated work clothing should not be allowed out of the workplace.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.

2.3 Other hazards

Adverse environmental effects

Contains no substance(s) known to have endocrine disrupting properties.
The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description

Base Oil and Additives

Hazardous ingredients

2-AMINOETHANOL ; REACH No. : 01-2119486455-28-0000 ; EC No. : 205-483-3; CAS No. : 141-43-5

Weight fraction : $\geq 1 - < 3 \%$
Classification 1272/2008 [CLP] : Skin Corr. 1B ; H314 Eye Dam. 1 ; H318 Acute Tox. 4 ; H302 Acute Tox. 4 ;
H312 Acute Tox. 4 ; H332 STOT SE 3 ; H335 Aquatic Chronic 3 ; H412
Specific Conc. Limits : STOT SE 3 ; H335: C $\geq 5 \%$

Alkylamine Polyol Alkylphosphate ; CAS No. : 1702655-09-1

Weight fraction : $\geq 1 - < 5 \%$
Classification 1272/2008 [CLP] : STOT RE 2 ; H373 Eye Irrit. 2 ; H319

1-phenoxypropan-2-ol ; REACH No. : 01-2119486566-23- ; EC No. : 212-222-7; CAS No. : 770-35-4

Weight fraction : $\geq 1 - < 5 \%$
Classification 1272/2008 [CLP] : Eye Irrit. 2 ; H319

Alcohols, C16-18 and C18-unsatd., ethoxylated ; REACH No. : 01-2119489407-26 ; EC No. : 500-236-9; CAS No. : 68920-66-1

Weight fraction : $\geq 1 - < 2,5 \%$
Classification 1272/2008 [CLP] : Skin Irrit. 2 ; H315 Aquatic Chronic 2 ; H411

Alkyl triamine ; EC No. : 223-362-3; CAS No. : 3855-32-1

Weight fraction : $\geq 0,5 - < 1 \%$
Classification 1272/2008 [CLP] : Acute Tox. 3 ; H311 Skin Corr. 1B ; H314 Acute Tox. 4 ; H302 Aquatic Chronic 3 ;
H412

DICYCLOHEXYLAMINE ; REACH No. : 01-2119493354-33-0000 ; EC No. : 202-980-7; CAS No. : 101-83-7

Weight fraction : $< 1 \%$
Classification 1272/2008 [CLP] : Acute Tox. 3 ; H301 Acute Tox. 3 ; H311 Skin Corr. 1B ; H314 Eye Dam. 1 ;
H318 Aquatic Acute 1 ; H400 Aquatic Chronic 1 ; H410

1,2-BENZISOTHIAZOL-3(2H)-ONE ; REACH No. : 01-2120761540-60-XXXX ; EC No. : 220-120-9; CAS No. : 2634-33-5

Weight fraction : $\geq 0,05 - < 0,25 \%$
Classification 1272/2008 [CLP] : Eye Dam. 1 ; H318 Acute Tox. 4 ; H302 Skin Irrit. 2 ; H315 Skin Sens. 1 ;
H317 Aquatic Acute 1 ; H400

Specific Conc. Limits : Skin Sens. 1 ; H317: C $\geq 0,05 \%$

2-N-BUTYL-BENZO[D]ISOTHIAZOL-3-ONE ; EC No. : 420-590-7; CAS No. : 4299-07-4

Weight fraction : $\geq 0,025 - < 0,1 \%$
Classification 1272/2008 [CLP] : Skin Corr. 1B ; H314 Eye Dam. 1 ; H318 Skin Sens. 1 ; H317 Aquatic Acute 1 ;
H400 Aquatic Chronic 1 ; H410

Specific Conc. Limits : (M Chronic=1) • (M Acute=10)

Further ingredients

The highly refined mineral oil contains less than 3% (w/w) DMSO-extract, according to IP 346 and is not considered to be carcinogenic.

Additional information

For full text of Hazard- and EU Hazard-statements: see SECTION 16.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : BVR301
Revision date : 12.01.2024
Print date : 03.12.2025

Version (Revision) : 6.0.1 (5.0.1)

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

When in doubt or if symptoms are observed, get medical advice. If unconscious but breathing normally, place in recovery position and seek medical advice.

Following inhalation

Remove victim out of the danger area. Remove casualty to fresh air and keep warm and at rest. Where appropriate artificial ventilation. In case of respiratory tract irritation, consult a physician.

In case of skin contact

Change contaminated, saturated clothing. After contact with skin, wash with plenty of water and soap. In case of skin irritation, consult a physician.

After eye contact

Rinse immediately carefully and thoroughly with eye-bath or water. Remove contact lenses, if present and easy to do. Continue rinsing. In case of eye irritation consult an ophthalmologist.

Following ingestion

Call a physician immediately. Rinse mouth thoroughly with water. Never give anything by mouth to an unconscious person or a person with cramps.

4.2 Most important symptoms and effects, both acute and delayed

No information available.

4.3 Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Foam, Extinguishing powder, Carbon dioxide (CO₂), Water spray jet, Water mist

Unsuitable extinguishing media

Strong water jet

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

In case of fire may be liberated: Carbon dioxide (CO₂), Carbon monoxide, Nitrogen oxides (NO_x), Phosphorus oxides, Smoke and other incomplete combustion products.

5.3 Advice for firefighters

Special protective equipment for firefighters

Wear self-contained breathing apparatus.

5.4 Additional information

Do not inhale explosion and combustion gases. Move undamaged containers from immediate hazard area if it can be done safely. Use water spray jet to protect personnel and to cool endangered containers. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Use personal protection equipment. Remove persons to safety. Avoid contact with skin, eyes and clothes. Provide adequate ventilation. Wear breathing apparatus if exposed to vapours/dusts/aerosols. Special danger of slipping by leaking/spilling product. Remove all sources of ignition.

6.2 Environmental precautions

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : BVR301
Revision date : 12.01.2024
Print date : 03.12.2025

Version (Revision) : 6.0.1 (5.0.1)

Cover drains. Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Make sure spills can be contained, e.g. in sump pallets or kerbed areas.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3 Methods and material for containment and cleaning up

For containment

Cover drains. Stop and contain spill/release if it can be done safely. If this cannot be done, allow fire to burn under control. Prevent spread over a wide area (e.g. by containment or oil barriers).

For cleaning up

Clear spills immediately. Wipe up with absorbent material (eg. cloth, fleece). Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Take up mechanically, placing in appropriate containers for disposal. Ventilate affected area. Clean contaminated articles and floor according to the environmental legislation.

6.4 Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Wear personal protection equipment (refer to section 8). Use only in well-ventilated areas. Handle and open container with care. Always close containers tightly after the removal of product. Avoid contact with skin, eyes and clothes. Do not breathe gas/fumes/vapour/spray. Keep away from sources of ignition - No smoking.

Protective measures

Measures to prevent fire

Only use the material in places where open light, fire and other flammable sources can be kept away.

Environmental precautions

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Shafts and sewers must be protected from entry of the product.

Advices on general occupational hygiene

When using do not eat, drink, smoke, sniff. Wash hands before breaks and after work. Do not put any product-impregnated cleaning rags into your trouser pockets. Use protective skin cream before handling the product.

7.2 Conditions for safe storage, including any incompatibilities

Packaging materials

Only use containers specifically approved for the substance/product.

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place. Protect containers against damage. Floors should be impervious, resistant to liquids and easy to clean.

Hints on joint storage

Keep away from: Oxidizing agent

Storage class (TRGS 510) : 10

Do not store together with

Food and feedingstuffs

Further information on storage conditions

Recommended storage temperature : 5 - 40°C / 40 - 105°F.

Protect against : Heat. UV-radiation/sunlight Frost

Storage stability : Product may be stored for up to 12 months under described conditions.

7.3 Specific end use(s)

None

SECTION 8: Exposure controls/personal protection

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : BVR301
Revision date : 12.01.2024
Print date : 03.12.2025

Version (Revision) : 6.0.1 (5.0.1)

8.1 Control parameters

Occupational exposure limit values

2,2',2''-NITRILOTRIETHANOL ; CAS No. : 102-71-6

Limit value type (country of origin) : AGW (D)

Limit value : 5 mg/m³

Version :

Limit value type (country of origin) : TRGS 900 (D)

Parameter : E: inhalable fraction

Limit value : 1 mg/m³

Peak limitation : 1(I)

Remark : Y

Version : 12.06.2023

2-AMINOETHANOL ; CAS No. : 141-43-5

Limit value type (country of origin) : TRGS 900 (D)

Limit value : 0,2 ppm / 0,5 mg/m³

Peak limitation : 1(I)

Remark : H, Sh, Y

Version : 12.06.2023

Limit value type (country of origin) : STEL (EC)

Limit value : 3 ppm / 7,6 mg/m³

Remark : Skin

Version : 09.03.2022

Limit value type (country of origin) : TWA (EC)

Limit value : 1 ppm / 2,5 mg/m³

Remark : Skin

Version : 09.03.2022

DICYCLOHEXYLAMINE ; CAS No. : 101-83-7

Limit value type (country of origin) : TRGS 900 (D)

Limit value : 0,7 ppm / 5 mg/m³

Peak limitation : 2(II)

Remark : H, Y

Version : 12.06.2023

DNEL-/PNEC-values

DNEL/DMEL

2,2',2''-NITRILOTRIETHANOL ; CAS No. : 102-71-6

Limit value type : DNEL worker (systemic)

Exposure route : Dermal

Exposure frequency : Long-term

Limit value : 6,3 mg/kg bw/d

Limit value type : DNEL worker (systemic)

Exposure route : Inhalation

Exposure frequency : Long-term

Limit value : 5 mg/m³

2-AMINOETHANOL ; CAS No. : 141-43-5

Limit value type : DNEL worker (systemic)

Exposure route : Dermal

Exposure frequency : Long-term

Limit value : 1 mg/kg

Limit value type : DNEL worker (systemic)

Exposure route : Inhalation

Exposure frequency : Long-term

Limit value : 3,3 mg/m³

Alcohols, C16-18 and C18-unsatd., ethoxylated ; CAS No. : 68920-66-1

Limit value type : DNEL worker (systemic)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : BVR301
Revision date : 12.01.2024
Print date : 03.12.2025

Version (Revision) : 6.0.1 (5.0.1)

Exposure route : Dermal
Exposure frequency : Long-term
Limit value : 2080 mg/kg bw/d
Limit value type : DNEL worker (systemic)
Exposure route : Inhalation
Exposure frequency : Long-term
Limit value : 294 mg/m³

1-phenoxypropan-2-ol ; CAS No. : 770-35-4

Limit value type : DNEL worker (systemic)
Exposure route : Dermal
Exposure frequency : Long-term
Limit value : 42 mg/kg bw/day
Limit value type : DNEL worker (systemic)
Exposure route : Inhalation
Exposure frequency : Long-term
Limit value : 25,7 mg/m³

DICYCLOHEXYLAMINE ; CAS No. : 101-83-7

Limit value type : DNEL worker (systemic)
Exposure route : Dermal
Exposure frequency : Long-term
Limit value : 0,1 mg/kg
Limit value type : DNEL worker (systemic)
Exposure route : Inhalation
Exposure frequency : Long-term
Limit value : 0,353 mg/m³

Remark

The DNEL may differ from an Occupational Exposure Limit (OEL) for the same chemical. OELs are considered to be safe exposure levels for a typical worker in an occupational setting for an 8-hour work shift, 40 hour work week, as a time weighted average (TWA) or a 15 minute short-term exposure limit (STEL). The Derived No Effect Level (DNEL) is an estimated safe level of exposure that is derived from toxicity data in accord with specific guidance within the European REACH regulation.

PNEC

2,2',2''-NITRILOTRIETHANOL ; CAS No. : 102-71-6

Limit value type : PNEC (Aquatic, freshwater)
Limit value : 0,32 mg/l
Limit value type : PNEC (Aquatic, marine water)
Limit value : 0,032 mg/l
Limit value type : PNEC (Sediment, freshwater)
Limit value : 1,7 mg/kg
Limit value type : PNEC (Sediment, marine water)
Limit value : 0,17 mg/kg
Limit value type : PNEC (Soil)
Limit value : 0,151 mg/kg

2-AMINOETHANOL ; CAS No. : 141-43-5

Limit value type : PNEC (Aquatic, freshwater)
Limit value : 0,085 mg/l
Limit value type : PNEC (Aquatic, marine water)
Limit value : 0,0085 mg/l
Limit value type : PNEC (Sediment, freshwater)
Limit value : 0,425 mg/kg
Limit value type : PNEC (Sewage treatment plant)
Limit value : 100 mg/l

Alcohols, C16-18 and C18-unsatd., ethoxylated ; CAS No. : 68920-66-1

Limit value type : PNEC (Aquatic, freshwater)
Limit value : 0,002 mg/l
Limit value type : PNEC (Aquatic, marine water)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : BVR301
Revision date : 12.01.2024
Print date : 03.12.2025

Version (Revision) : 6.0.1 (5.0.1)

Limit value : 0,002 mg/l
Limit value type : PNEC (Sediment, freshwater)
Limit value : 6,33 mg/kg
Limit value type : PNEC (Soil)
Limit value : 1 mg/kg
Limit value type : PNEC (Sewage treatment plant)
Limit value : 10000 mg/l
DICYCLOHEXYLAMINE ; CAS No. : 101-83-7
Limit value type : PNEC (Aquatic, freshwater)
Limit value : 0,00032 mg/l
1-phenoxypropan-2-ol ; CAS No. : 770-35-4
Limit value type : PNEC (Aquatic, freshwater)
Limit value : 0,1 mg/l
Limit value type : PNEC (Aquatic, marine water)
Limit value : 0,01 mg/l
DICYCLOHEXYLAMINE ; CAS No. : 101-83-7
Limit value type : PNEC (Aquatic, marine water)
Limit value : 3E-05 mg/l
Limit value type : PNEC (Sediment, freshwater)
Limit value : 0,00529 mg/kg
1-phenoxypropan-2-ol ; CAS No. : 770-35-4
Limit value type : PNEC (Sediment, freshwater)
Limit value : 0,38 mg/kg dry weight
Limit value type : PNEC (Sediment, marine water)
Limit value : 0,038 mg/kg dry weight
DICYCLOHEXYLAMINE ; CAS No. : 101-83-7
Limit value type : PNEC (Sewage treatment plant)
Limit value : 108 mg/l
1-phenoxypropan-2-ol ; CAS No. : 770-35-4
Limit value type : PNEC (Sewage treatment plant)
Limit value : 10 mg/l

8.2 Exposure controls

Appropriate engineering controls

Use only in well-ventilated areas. If handled uncovered, arrangements with local exhaust ventilation should be used if possible. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means. Technical measures and the application of suitable work processes have priority over personal protection equipment.

Personal protection equipment

Personal protective equipment selections vary based on potential exposure conditions such as applications, handling practices, concentration and ventilation. Information on the selection of protective equipment for use with this material, as provided below, is based upon intended, normal usage.

Eye/face protection

Eye glasses with side protection EN 166

Skin protection

Hand protection

The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. Tested protective gloves must be worn: DIN EN 374 Do not wear gloves near rotary machines and tools.

Suitable material :

Wearing time with permanent contact:

Material: NBR (Nitrile rubber), CR (polychloroprene, chloroprene rubber),

Thickness of the glove material: 0,70 mm

Breakthrough time (maximum wearing time): > 480 min

Wearing time with occasional contact (splashes):

Material: NBR (Nitrile rubber), CR (polychloroprene, chloroprene rubber),

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : BVR301
Revision date : 12.01.2024
Print date : 03.12.2025

Version (Revision) : 6.0.1 (5.0.1)

Thickness of the glove material: 0,40 mm
Breakthrough time (maximum wearing time): > 30 min

Unsuitable material : PVA (Polyvinyl alcohol),

Breakthrough time (maximum wearing time) : For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Check leak tightness/impermeability prior to use.

Body protection

If prolonged or repeated contact is likely, chemical, and oil resistant clothing is recommended.

Respiratory protection

Usually no personal respirative protection necessary. If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Respiratory protection necessary at: exceeding exposure limit values, insufficient ventilation, aerosol or mist formation.

General information

When using do not eat, drink, smoke, sniff. Wash hands before breaks and after work. Do not put any product-impregnated cleaning rags into your trouser pockets. Wash contaminated clothing prior to re-use. Apply skin care products after work.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : Liquid

Colour : yellow

Odour : characteristic

Safety characteristics

Melting point/freezing point :			No data available	
Initial boiling point and boiling range :	(1013 hPa)	>	100 °C	
Flammability:			flammable	
Lower explosion limit :			No data available	
Upper explosion limit :			No data available	
Flash point :		>	100 °C	DIN EN ISO 2592
Auto-ignition temperature :			No data available	
Decomposition temperature :			not determined	
pH :	(20 °C / 5 Weight-%)		9,7	DIN 51369
Kinematic viscosity :	(20 °C)	approx.	200 mm ² /s	DIN EN ISO 3104
Water solubility :	(20 °C)		miscible	
log P O/W :			not applicable	
Vapour pressure :	(20 °C)		No data available	
Density :	(15 °C)		0,988 g/cm ³	DIN EN ISO 12185
Relative vapour density :	(20 °C)		No data available	

9.2 Other information

None

SECTION 10: Stability and reactivity

10.1 Reactivity

No information available.

10.2 Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3 Possibility of hazardous reactions

No known hazardous reactions.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : BVR301
Revision date : 12.01.2024
Print date : 03.12.2025

Version (Revision) : 6.0.1 (5.0.1)

10.4 Conditions to avoid

No information available.

10.5 Incompatible materials

Oxidising agent, strong.

10.6 Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicological data are not available. The statement is derived from the properties of the single components.

Acute toxicity

Based on available data, the classification criteria are not met.

Acute oral toxicity

Parameter :	LD50 (2-AMINOETHANOL ; CAS No. : 141-43-5)
Exposure route :	Oral
Species :	Rat
Effective dose :	1000 mg/kg
Parameter :	LD50 (1-phenoxypropan-2-ol ; CAS No. : 770-35-4)
Exposure route :	Oral
Species :	Rat
Effective dose :	> 2000 mg/kg
Parameter :	LD50 (Alcohols, C16-18 and C18-unsatd., ethoxylated ; CAS No. : 68920-66-1)
Exposure route :	Oral
Species :	Rat
Effective dose :	> 2000 mg/kg
Parameter :	LD50 (DICYCLOHEXYLAMINE ; CAS No. : 101-83-7)
Exposure route :	Oral
Species :	Rat
Effective dose :	200 mg/kg

Acute dermal toxicity

Parameter :	LD50 (2-AMINOETHANOL ; CAS No. : 141-43-5)
Exposure route :	Dermal
Species :	Rabbit
Effective dose :	1025 mg/kg
Method :	literature
Parameter :	LD50 (1-phenoxypropan-2-ol ; CAS No. : 770-35-4)
Exposure route :	Dermal
Species :	Rat
Effective dose :	> 2000 mg/kg
Parameter :	LD50 (DICYCLOHEXYLAMINE ; CAS No. : 101-83-7)
Exposure route :	Dermal
Species :	Rabbit
Effective dose :	200 - 316 mg/kg

Acute inhalation toxicity

Parameter :	LC50 (1-phenoxypropan-2-ol ; CAS No. : 770-35-4)
Exposure route :	Inhalation (dust/mist)
Species :	Rat
Effective dose :	> 5,4 mg/l

Corrosion

Irritating to eyes and skin.

Skin corrosion/irritation

Parameter :	Skin corrosion/irritation (2-AMINOETHANOL ; CAS No. : 141-43-5)
-------------	---

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : BVR301
Revision date : 12.01.2024
Print date : 03.12.2025

Version (Revision) : 6.0.1 (5.0.1)

Species : Rabbit
Result : corrosive
Method : OECD 404
Parameter : Skin corrosion/irritation (1-phenoxypropan-2-ol ; CAS No. : 770-35-4)
Species : Rabbit
Result : Slightly irritant but not relevant for classification
Parameter : Skin corrosion/irritation (Alcohols, C16-18 and C18-unsatd., ethoxylated ; CAS No. : 68920-66-1)
Species : Rabbit
Result : irritating
Method : OECD 404
Parameter : Skin corrosion/irritation (DICYCLOHEXYLAMINE ; CAS No. : 101-83-7)
Species : Rabbit
Result : corrosive

Serious eye damage/eye irritation

Parameter : Serious eye damage/eye irritation (2-AMINOETHANOL ; CAS No. : 141-43-5)
Species : Rabbit
Result : corrosive
Method : OECD 405
Parameter : Serious eye damage/eye irritation (1-phenoxypropan-2-ol ; CAS No. : 770-35-4)
Species : Rabbit
Result : irritating
Parameter : Serious eye damage/eye irritation (Alcohols, C16-18 and C18-unsatd., ethoxylated ; CAS No. : 68920-66-1)
Species : Rabbit
Result : Mild effects but not relevant for classification.
Method : OECD 405
Parameter : Serious eye damage/eye irritation (DICYCLOHEXYLAMINE ; CAS No. : 101-83-7)
Species : Rabbit
Result : corrosive

Respiratory or skin sensitisation

May cause sensitization by skin contact.

Skin sensitisation

Parameter : Skin sensitisation (1-phenoxypropan-2-ol ; CAS No. : 770-35-4)
Species : Guinea pig
Result : Not sensitising.
Parameter : Skin sensitisation (Alcohols, C16-18 and C18-unsatd., ethoxylated ; CAS No. : 68920-66-1)
Species : Guinea pig
Result : not sensitizing
Method : OECD 406

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Carcinogenicity

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

STOT SE 1 and 2

Based on available data, the classification criteria are not met.

STOT-repeated exposure

STOT RE 1 and 2

Based on available data, the classification criteria are not met.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : BVR301
Revision date : 12.01.2024
Print date : 03.12.2025

Version (Revision) : 6.0.1 (5.0.1)

Aspiration hazard

Based on available data, the classification criteria are not met. For viscosity data, see section 9.

11.2 Information on other hazards

No information available.

SECTION 12: Ecological information

12.1 Toxicity

For the product ecotoxicological data are not available. The ecotoxicological properties of this mixture are determined by the ecotoxicological properties of the single components (see section 3).

Aquatic toxicity

Harmless to aquatic organisms.

Acute (short-term) fish toxicity

Parameter :	LC50 (2-AMINOETHANOL ; CAS No. : 141-43-5)
Species :	Cyprinus carpio (Common Carp)
Effective dose :	> 100 mg/l
Exposure time :	96 h
Method :	OECD 203
Parameter :	LC50 (1-phenoxypropan-2-ol ; CAS No. : 770-35-4)
Species :	Pimephales promelas (fathead minnow)
Effective dose :	> 100 mg/l
Method :	OECD 203
Parameter :	LC50 (Alcohols, C16-18 and C18-unsatd., ethoxylated ; CAS No. : 68920-66-1)
Species :	Danio rerio (zebrafish)
Effective dose :	10 - 100 mg/l
Exposure time :	96 h
Method :	OECD 203
Parameter :	LC50 (DICYCLOHEXYLAMINE ; CAS No. : 101-83-7)
Species :	Leuciscus idus (golden orfe)
Effective dose :	12 mg/l
Exposure time :	96 h
Method :	OECD 203

Acute (short-term) toxicity to crustacea

Parameter :	EC50 (2-AMINOETHANOL ; CAS No. : 141-43-5)
Species :	Daphnia magna (Big water flea)
Effective dose :	65 mg/l
Exposure time :	48 h
Parameter :	EC50 (1-phenoxypropan-2-ol ; CAS No. : 770-35-4)
Species :	Daphnia magna (Big water flea)
Effective dose :	> 370 mg/l
Method :	OECD 202
Parameter :	EC50 (Alcohols, C16-18 and C18-unsatd., ethoxylated ; CAS No. : 68920-66-1)
Species :	Daphnia magna (Big water flea)
Effective dose :	51 mg/l
Exposure time :	48 h
Method :	OECD 202
Parameter :	EC50 (DICYCLOHEXYLAMINE ; CAS No. : 101-83-7)
Species :	Daphnia magna (Big water flea)
Effective dose :	8 mg/l
Exposure time :	48 h
Method :	OECD 202

Acute (short-term) toxicity to algae and cyanobacteria

Parameter :	EC50 (2-AMINOETHANOL ; CAS No. : 141-43-5)
Species :	Scenedesmus subspicatus

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : BVR301
Revision date : 12.01.2024
Print date : 03.12.2025

Version (Revision) : 6.0.1 (5.0.1)

Effective dose : 22 mg/l
Exposure time : 72 h
Parameter : EC50 (1-phenoxypropan-2-ol ; CAS No. : 770-35-4)
Species : Desmodemus subspicatus
Effective dose : > 100 mg/l
Parameter : EC50 (Alcohols, C16-18 and C18-unsatd., ethoxylated ; CAS No. : 68920-66-1)
Species : Scenedesmus subspicatus
Effective dose : > 100 mg/l
Exposure time : 72 h
Parameter : EC50 (DICYCLOHEXYLAMINE ; CAS No. : 101-83-7)
Species : Scenedesmus subspicatus
Effective dose : 3,3 mg/l
Exposure time : 72 h
Method : OECD 201

12.2 Persistence and degradability

Abiotic degradation

Poorly eliminated from water.

Biodegradation

Part of the components is biodegradable.

12.3 Bioaccumulative potential

No indication of bioaccumulation potential.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6 Endocrine disrupting properties

No information available.

12.7 Other adverse effects

No information available.

12.8 Additional ecotoxicological information

Do not allow uncontrolled discharge of product into the environment.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Directive 2008/98/EC (Waste Framework Directive)

Consult the appropriate local waste disposal expert about waste disposal. Dispose of waste according to applicable legislation.

Before intended use

Waste codes/waste designations according to EWC/AVV

12 01 07* (Mineral-based machining oils free of halogens (except emulsions and solutions))

After intended use

Waste codes/waste designations according to EWC/AVV

12 01 09* (Machining emulsions and solutions free of halogens)

Remark

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process. However, deviation from the intended use and/or the presence of any potential contaminants may require an alternative waste disposal code to be assigned by the end user.

Additional information

Non-contaminated packages may be recycled.

Empty containers may contain residue and can be dangerous. Do not attempt to refill or clean containers without

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : BVR301
Revision date : 12.01.2024
Print date : 03.12.2025

Version (Revision) : 6.0.1 (5.0.1)

proper instructions. Do not pressurise, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition.

SECTION 14: Transport information

14.1 UN number or ID number

No dangerous good in sense of these transport regulations.

14.2 UN proper shipping name

No dangerous good in sense of these transport regulations.

14.3 Transport hazard class(es)

No dangerous good in sense of these transport regulations.

14.4 Packing group

No dangerous good in sense of these transport regulations.

14.5 Environmental hazards

No dangerous good in sense of these transport regulations.

14.6 Special precautions for user

None

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Authorisations and/or restrictions on use

Restrictions on use

Regulation (EC) No. 1907/2006 (REACH), Annex XVII (restrictions)

Use restriction according to REACH annex XVII, no. : 3, 75

National regulations

Technische Anleitung zur Reinhaltung der Luft (TA-Luft)

Weight fraction (Number 5.2.5. I) : < 5 %

Water hazard class

Classification according to AwSV - Class : 1 (Slightly hazardous to water)

Additional information

Berufsgenossenschaftliche Regeln (DGUV-Regeln)

The product corresponds with TRGS 611.

15.2 Chemical Safety Assessment

No information available.

SECTION 16: Other information

16.1 Indication of changes

None

16.2 Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : BVR301
Revision date : 12.01.2024
Print date : 03.12.2025

Version (Revision) : 6.0.1 (5.0.1)

CAS: Chemical Abstracts Service (division of the American Chemical Society)
GHS: Globally Harmonized System on the Classification and Labelling of Chemicals
CLP: Regulation on Classification, Labelling and Packaging of Substances and Mixtures,
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
EC50: Effective concentration, 50 percent
DNEL: Derived No Effect Level
PNEC: Predicted No Effect Concentration
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

16.3 Key literature references and sources for data

Sources of information used in preparing this SDS included one or more of the following: Product Dossiers and SDS from suppliers, complemented by public sources, as appropriate (GESTIS, the EU IUCLID Data Base, U.S. NTP publications, e.g.).

16.4 Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

No information available.

16.5 Relevant H- and EUH-phrases (Number and full text)

H301	Toxic if swallowed.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

16.6 Training advice

Provide adequate information, instruction and training for operators.

16.7 Additional information

None

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.